



Fosroc Nitotile GP

Polymer modified tile adhesive

Uses

Nitotile GP is a high quality adhesive for the permanent fixing of ceramic tiles. It can also be used for fixing of insulating and acoustic boards based on expanded polystyrene etc. Typical uses include :

- Wet areas - kitchens and bathrooms
- Tile claddings

Advantages

- Tropical grade to suit Middle East working conditions
- Good open wet time
- Good slip resistance
- High adhesive bond strength
- Water proof
- Good slip resistance
- Can be used in totally submerged conditions

Standards compliance

Nitotile GP conforms to BS5980 Class AA Type 1 and suitability for contact with potable water as per BS 6920 Part 1.

Description

Nitotile GP cementitious based powder is available in grey or white colour.

Technical support

Fosroc offers a comprehensive technical support service to specifiers, end users and contractors. It is also able to offer on-site technical assistance, an AutoCAD facility and dedicated specification assistance in locations all over the world.

Instructions for use

Surface preparation

All surfaces must be sound and thoroughly clean before Nitotile GP is applied. All traces of grease or oil must be removed with a chemical degreaser. All loose particles of mortar, old wallpaper, paint etc. must be physically removed.

Surfaces

Nitotile GP can be applied directly on concrete, cement screeds, and cement or lime mortar. Special attention must be given to new construction prior to commencing tiling. Tiles should not be placed on concrete or blockwork until all shrinkage movement has taken place.

To use Nitotile GP on gypsum or gypsum board substrates, diluted Nitobond PVA (1 : 3 with water) should be applied to the surface of the gypsum or gypsum board prior to application of Nitotile GP.

Mixing

5 litres of water is required for each 20kg bag, and 6.25 litres of water is required for each 25 kg bag of Nitotile GP. A slow speed drill fitted with a Fosroc Mixing Paddle (MR4) is recommended. Add powder to water and mix for 3 minutes, until a uniform and lump-free consistency is achieved.

Application

Nitotile GP should be spread on the substrate to a uniform thickness of 2-3mm, and then combed horizontally.

Place tiles firmly into adhesive bed, ensuring good contact with a twisting motion. Only apply to areas which can be tiled in the adhesive's open wet time (up to 1m² at a time).

Joints

It is recommended that when fixing ceramic tiles, a minimum spacing of 2mm be left around each tile.

Finishing

Remove excess adhesive with a damp cloth before material has set. Joint grouting with Nitotile Grout**† may be commenced 24 hours after tiles have been laid.

Cleaning

Nitotile GP should be removed from tools, equipment and mixers with clean water immediately after use. Cured material can only be removed mechanically.

Fosroc Nitotile GP

Limitations

Nitotile GP should not be used when the temperature is below 5°C and falling. The product should not be exposed to moving water during application. If any doubt arise concerning temperature or substrate conditions, consult your local Fosroc office.

Estimating

Supply

Nitotile GP	: 25 kg bags
--------------------	--------------

Yield

Nitotile GP	: Approx. 18.1 litres/ 25kg bag
--------------------	---------------------------------

Note : Actual yield will vary according to water addition

Storage

Shelf life

All products have a shelf life of 12 months if kept in a dry store in the original, unopened bags.

Storage conditions

Store in dry conditions in the original, unopened bags or packs. If stored at high temperature and / or high humidity conditions the shelf life may be reduced.

Precautions

Health and safety

Nitotile GP contains cement powders which, when mixed with water or upon becoming damp, release alkalis which can be harmful to the skin.

During use, avoid inhalation of the dust and contact with the skin or eyes. Wear suitable protective clothing - eye protection, gloves and respiratory equipment (particularly in confined spaces).

The use of barrier creams to provide additional skin protection is also advised. In case of contact with the skin, rinse with plenty of clean water, then cleanse thoroughly with soap and water.

In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. If swallowed seek medical attention immediately - do **not** induce vomiting.

Fire

Nitotile GP is non-flammable

Additional information

Nitotile GP is part of a range of Fosroc tile adhesive and tile grouts. In addition, Fosroc manufactures a range of complementary products which includes waterproofing membranes, joint sealants, grouting, anchoring and specialised flooring materials. Additionally, a wide range of products specifically designed for the repair and refurbishment of damaged reinforced concrete is available. This includes hand-placed and spray grade repair mortars, fluid micro-concretes, chemical resistant epoxy mortars and a comprehensive package of protective coatings.

For further information please contact your local Fosroc office.

* Denotes the trademark of Fosroc International Limited

† See separate data sheet



Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Service. **All Fosroc datasheets are updated on a regular basis. It is the user's responsibility to obtain the latest version.**

Head Office

telephone: (+9714) 2039699

fax: (+9714) 2859649

email: agf@fosroc.com

Regional offices

Abu Dhabi, Al Gurg Fosroc
Bahrain, YBA Kanoo
Kuwait, Boodai
Oman, Al Amana
Qatar, Tadmur

telephone: 673 1779
telephone: 17738200
telephone: 4817618
telephone: 24815080
telephone: 4432365

fax: 673 1449
fax: 17732828
fax: 4832124
fax: 24817554
fax: 4419517

email: abudhabi@fosroc.com
email: bahrain@fosroc.com
email: kuwait@fosroc.com
email: oman@fosroc.com
email: qatar@fosroc.com

Al Gurg Fosroc LLC

Post Box 657, Dubai
United Arab Emirates

www.fosroc.com

